

IM-Tanks

IM-1250

The Infiltrator IM-1250 is a lightweight, strong and durable septic tank. This watertight tank design is offered with Infiltrator's line of custom-fit EZsnap risers and heavy-duty lids. Infiltrator injection molded tanks provide a revolutionary improvement in plastic tank design, offering exceptional long-term strength and watertightness.



IM-1250

Benefits



Strong injection molded polypropylene construction



Lightweight plastic construction and inboard lifting lugs allow for easy delivery and handling



Integral heavy-duty green lids that interconnect with EZsnap risers, Safety Star secondary safety lid system, and pipe riser



Structurally reinforced access ports eliminate distortion during installation and pump-outs



Reinforced structural ribbing and fiberglass bulkheads offer additional strength



Can be installed with 6" to 48" (152 to 1,219 mm) of cover




Suitable for use as a septic tank, pump tank, or rain-water (non-potable) tank



No special water filling requirements are necessary
The tank may be backfilled with suitable native soil.

TANK CUTAWAY




Infiltrator
Water Technologies
Part of **ADS**


infiltratorwater.com • (800) 221-4436

IM-1250 General Specifications and Illustrations


The IM-1250 is an injection molded two-piece mid-seam polypropylene tank. The injection molded design of the IM-1250 allows for a mid-seam joint that has precise dimensions for accepting an engineered EPDM gasket. The engineered mid-seam joint accepts a continuous loop EPDM gasket. Infiltrator's EPDM gasket design utilizes technology and materials from the sanitary sewer pipe industry to deliver a reliable watertight seal. The two-piece design is permanently fastened using a system of molded-in alignment dowels and locking




TOP VIEW



SIDE VIEW



END VIEW



MID-HEIGHT SEAM SECTION

Must be backfilled and installed in accordance with the Infiltrator IM- and CM-Series Septic Tank General

Installation Instructions. For shallow ground water conditions reference the Infiltrator IM- and CM-Series Tank Buoyancy Control Guidance.

Please visit www.infiltratorwater.com or scan QR code for the latest information.

IM-1250

Working Capacity	1,278 GAL (4,839 L)
Total Capacity	1,480 GAL (5,602 L)
Airspace	16.30%
Length	154" (3,911 mm)
Width	61.7" (1,567 mm)
Length-to-Width Ratio	2.8 : 1
Height	54.6" (1,387 mm)
Liquid Level	44" (1,118 mm)
Invert Drop	3" (76 mm)
Fiberglass Supports	4
Compartments	1 or 2
Maximum Burial Depth	48" (1,219 mm)
Minimum Burial Depth	6" (152 mm)
Maximum Pipe Diameter	4" (102 mm)
Weight	405 lbs (184 kg)

Contact Infiltrator's Technical Services Department for assistance at 1-800-221-4436 or info@infiltratorwater.com